



SILVER

A New Generation of Underlayments

TECHNICAL DATA SHEET

FT SYNTHETICS SILVER		
General Specifications		
	SILVER	15 lb Felt
Width inch	48	36
Weight per roll	22 lb	45 lb
Length in feet	250	144
Rolls per Pallet (44 x 44)	49	25
Rolls per Truckload - 36 Skids	1764	1000
Rolls Required per 1,000 Sq feet	1	2.5
100% recyclable	Yes	No
Material Composition	Polyolefin	Asphalt
UV Resistance	3 Months	None
Breaking Strength ASTM D 5034 MD	90.4 lb (41.0 kg)	NA
Breaking Strength ASTM D 5034 CD	86.0 lb (39.0 kg)	NA
Tear Strength ASTM D4533 MD	48.0 lb (21.8 kg)	NA
Tear Strength ASTM D4533 CD	51.0 lb (23.1 kg)	NA
Water shower Exposure ASTM D 4869	Pass	NA
Permeability ASTM E96	<0.05 Perms	5 Perms
Mullen Burst	113 psi	NA
Nominal Thickness ASTM D1777	12 mils	21 mils
Temperature Range	-40°F to 240°F	
Enhanced Slip Resistant Surface	GRIPSPOT™	Basic
Limited Warranty	20 Years	None

The Data shown above is based on the test averages and independent test reports. There can be a +/-10% variation in the individual test results. This report should not be considered as a warranty for the manufacturer. The manufacturer is not responsible for the misrepresentation or misinterpretation of the data by the reader. Please find out more about the product by calling 1-844-353-9839 or visit www.ftsyn.com. GRIPSPOT™ is a trademark of FT Synthetics Inc.

ASTM D226-97
ASTM D4869
CAN/CSA A123.3



CAN/ CSA A220.1
ASTM E108
CCRR 1028
AC188



12179 - 86th Avenue
Surrey BC V3W 3H8
Canada

Toll Free Ph: 1-844-353-9839
Phone: 604-594-3439
Fax: 604-594-3589
www.ftsyn.com