PABCO Premier[®]

Technical Data Sheet



PABCO Premier[®] provides dependable protection for your project: from new construction to upgrading an existing roof. This architectural shingle is a premium laminated shingle option available for first homes and dream homes alike, so you can have confidence in your choice.

Our heavyweight glass mat is saturated with quality asphalt and coated with colored mineral granules to produce 10 color options. Cut with our tapered design to help alleviate debris and patterning, two layers are then laminated together to develop its appearance. Trust the premium option and choose PABCO Premier.

TECHNICAL DETAIL	DATA
Category	Architectural Laminated Fiberglass
Weight per Square (nominal)	255 lbs
Weather Exposure	5 5/8"
Offset	5 5/8" (may be applied L to R, or R to L)
Shingles per Square (approx.)	64
Bundles per Square (approx.)	4
Bundles per Pallet	68

WARRANTY*	
Original Homeowner	Limited Lifetime
Subsequent Homeowners	30 Years Fully Transferable
Non-Prorated Coverage	15 Years
Wind Resistance (Standard Application 110 mph)	15 Years
Wind Resistance (High Wind Application – 130 mph)	15 Years
Algae Resistance (Featuring Algae Defender®)	Limited Lifetime

DESIGNATION NUMBER	APPLICABLE STANDARD
ASTM D3462	Standard Specification for Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
ASTM D3018	Type I Standard Specification for Class A Asphalt Shingles Surfaced with Mineral Granules
CSA Standard A123.5	Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
UL 790	Class A Fire Resistance
ASTM E108	Class A Fire Resistance
ASTM D3161	Class F Wind Resistance
ASTM D7158	Class H Wind Resistance
ESR-1717	ICC-ES Evaluation Report



Detailed Installation instructions at <u>www.pabcoroofing.com/literature</u>.

*Single Family Residences only. See PABCO®'s Limited Shingle Warranty for details and other structures.

PABCO Premier[®] Technical Data Sheet 1476 Thorne Rd, Tacoma, WA 98421 253.272.0374 | www.pabcoroofing.com