ISO 9001 - 2008
REGISTERED
FACILITY

STOCK NO. 7920030

JULY, 2016

ARMOURVENT BASE

This SBS modified bituminous base sheet is specially designed for partial adhesion to the roof substrate. A unique pattern of discontinuous modified bituminous strips provides for easy installation, stress distribution from substrate movements, and primarily aids venting (vapour diffusion) of any moisture below the membrane. Thus, the product minimizes roofing system blisters that may form due to un-vented moisture build-up. The top surface is finished with a micro-perforated poly-film to allow heat welding application of the cap sheet, and also includes a self-adhesive selvage lap. When used with a cap sheet, this product will easily satisfy the requirements of CGSB-37.56-M, as well as the requirements of ASTM D6163 Type I Grade S. IKO's roofing products are produced and designed with consideration for environmental responsibility and sustainability, incorporating quality recycled components whenever possible, manufactured in facilities that comply with the most stringent government environmental regulations, and can therefore be a part of any "green" construction project.

CHARACTERISTIC	UNITS	NOMINAL VALUE	SPECIFICATION	TEST METHOD	STANDARD LIMITS
ROLLS PER PALLET:	-	32	-	-	N/A
PALLET SIZE:	cm (in)	132 x 112 (52 x 44)	-	-	-
LENGTH:	m (ft)	12 (39.4)	-	-	± 1%
WIDTH:	mm (in)	1000 (39 3/8)	-	-	± 3 (1/8)
WEIGHT:	kgs (lbs)	32 (70)	-	-	-
THICKNESS:	mm (mils)	2.8 (110)	ASTM D1970	ASTM D751	MIN: 1.0 (40)
LINES:	mm (in)	90 (3.5)	-	-	-
COLD FLEX:	°C (°F)	-30 (-22)	ASTM D1970	ASTM D1970	MIN: -29 (-20)