



# GAFGLAS<sup>®</sup>

## FLEXPLY<sup>™</sup> 6



### Description

FlexPly<sup>™</sup>6 is a premium-performing fiberglass Type VI roofing felt. Its revolutionary flexible design provides:

- Maximum strength and stability
- Improved conformance to underlying substrates
- Ease of installation compared to typical Type VI felts
- Long-term performance for peace of mind

### Uses

FlexPly 6 should be specified as a ply felt in the construction of all premium quality built-up roofs, including:

- System guarantees are available for up to 20 years.
- Most GAF Composite Roof<sup>™</sup> systems
- Also appropriate for use as a base sheet and in the construction of flashing membranes.

### Advantages

- Revolutionary flexible design—Rolls out easier and lays flatter, minimizing the danger of air pockets and trapped moisture during installation
- Saves labor—Open pore design actively absorbs asphalt, installs faster than other Type VI felts

### Advantages (Continued)

- Quality installation—Enhanced porosity encourages proper absorption of asphalt for long lasting system performance up to 20 years
- Proprietary Micro Weave<sup>®</sup> Core—Provides superior tensile strength and dimensional stability, for greater resistance to splitting and cracking
- Superior wind resistance—Selected systems have FMRC Class 1-180 rating
- Highest fire rating—For use in UL, ULC Class A rated assemblies
- Can be used in all climate zones

### Applicable Standards

Meets ASTM D2178, Type VI
FM Approved
ICC ESR#1274
Miami-Dade County Product Control Approval
State of Florida Product Approval
Texas Department of Insurance
UL/ULc Listed

### Products Specifications (nominal)

Roll Size	5 squares (531 gross sq.ft.) (49.3m <sup>2</sup> )
Roll Length	161.8' (49.3m)
Roll Width	39.375" (1.0m)
Approx. Roll Weight	44 lbs (20.0kg)