



RUBEROID[®] TORCH GRANULE MEMBRANE

Description

RUBEROID[®] Torch Granule Membrane is a tough, resilient modified bitumen membrane manufactured to stringent GAF specifications. Its core is a strong, resilient, non-woven polyester mat that is coated with weather resistant APP polymer modified asphalt.

Uses

RUBEROID[®] Torch Granule Membrane is designed for new roofing and reroofing applications as well as flashings. RUBEROID[®] Torch Granule Membrane is also an ideal product for repairs of built-up roofing membrane or other modified bitumen systems.

Advantages

- System guarantees available for up to 15 years; select system constructions available with up to 20-year guarantee coverage.*
- Cost effective—The installed cost of RUBEROID[®] Torch Granule Membrane is less than most single-ply systems on the market today.
- Light weight—Installed roof designs weigh less than 2 pounds per square foot (9.8 kg/m²).
- Resilient—RUBEROID[®] Torch Granule Membrane polyester mat core allows it to resist splits and tears due to its pliability and elongation characteristics.

This product meets or exceeds the following ASTM D6222, Type I, Grade G, minimum requirements:

Property	Test Method	Value
Tensile Strength @ 0°F (min), lbf/in	ASTM D5147	60
Elongation @ 0°F (min), %	ASTM D5147	10
Low Temperature Flexibility (max), °F	ASTM D5147	32
Tear Strength (min), lbf	ASTM D5147	70
Dimensional Stability, (max) %	ASTM D5147	<0.5

* See applicable guarantee for complete coverage and restrictions.

Advantages (Continued)

- Durable—Specially formulated modified asphalt for lasting performance.
- RUBEROID[®] Torch Granule Membrane is manufactured by GAF, a company with over 125 years in the roofing business.
- Available in smooth surface and two granular colors: black and white.

Applicable Standards

Meets ASTM D6222, Type I, Grade G

FM Approved

HUD Material Release #1216A

Miami-Dade County Product Control Approved

UL/ULC Listed

*See Modified Bitumen and Built-Up Roofing Application and Specification Manual or UL Directory for specific approval.

Product Specifications (nominal)

Roll Size	1 square (106.5 gross sq. ft.) (9.8 m ²)
Roll Length	32.3' (9.8 m)
Roll Width	39.58" (.625 m)
Approx. Roll Weight	99 lb (44.9 kg)
Product Thickness	0.160" (4 mm)

