

Tahoma®

Technical Data Sheet



Looking for a traditional shingle option? Our Tahoma® 3-tab asphalt shingle aligns with the architecture and design of varying home styles, providing you the versatility you want, at a price that won't break the bank.

Available in nine color options, with a 30-year warranty and optional Algae Defender® on many colors, Tahoma is ideal for homeowners desiring a uniform design and protection for years to come.

TECHNICAL DETAIL	DATA
Category	3-Tab Fiberglass
Weight per Square (nominal)	205 lbs
Weather Exposure	5 5/8"
Offset	5 5/8" (may be applied L to R, or R to L)
Shingles per Square (approx.)	65
Bundles per Square (approx.)	3
Bundles per Pallet	64

WARRANTY*	
Original Homeowner	30 Years Fully Transferable
Subsequent Homeowners	30 Years Fully Transferable
Non-Prorated Coverage	5 Years
Wind Resistance (Standard Application 110 mph)	5 Years
Wind Resistance (High Wind Application – 130 mph)	20 Years
Algae Resistance (Featuring Algae Defender®)	Limited Lifetime

DESIGNATION NUMBER	APPLICABLE STANDARD
ASTM D3462	Standard Specification for Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
ASTM D3018	Type I Standard Specification for Class A Asphalt Shingles Surfaced with Mineral Granules
CSA Standard A123.5	Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
UL 790	Class A Fire Resistance
ASTM E108	Class A Fire Resistance
ASTM D3161	Class F Wind Resistance
ASTM D7158	Class H Wind Resistance
ESR-1717	ICC-ES Evaluation Report



Detailed Installation instructions at www.pabcoroofing.com/literature.

*Single Family Residences only. See PABCO®'s Limited Shingle Warranty for details and other structures.