



**PRO-20**  
**FT SYNTHETICS**

# TECHNICAL DATA SHEET

## PRO-20 : TECHNICAL DATA SHEET

Specification & Standard	PRO20	#15 Felt
Length / width per roll	42" x 286ft	36" x 144ft
Weight / sq. ft. per roll	21 lbs (9 kg) / 1000 sq. ft.	45lbs / 432 sq. ft.
Rolls per pallet (42" x 42")	49	25
Rolls per truckload - 40 pallets	1960	1000
Rolls required per 1,000 Sq feet	1	2.5
100% recyclable	Yes	No
Material composition	Polyolefin	Asphalt
UV resistance	90 days	None
Breaking strength ASTM D 5034 MD / CD	101 lb (45 kg) / 96 lb (44 kg)	NA
Tear strength ASTM D4533 MD / CD	25 lb (11 kg) / 23 lb (10 kg)	NA
Water shower exposure ASTM D 4869	Pass	NA
Permeability ASTM E96	<0.05 Perms	6 Perms
Mullen Burst	102 psi	NA
Nominal thickness ASTM D1777	10 mils	21 mils
Temperature range	-40° F to 240° F	
Enhanced slip resistant surface	Excellent	Basic
Limited warranty	20 years	None

The data shown above is based on the test averages and independent test reports. There can be a +/-10% variation in the individual test results. This report should not be considered as a warranty for the manufacturer. The manufacturer is not responsible for the misrepresentation or misinterpretation of the data by the reader. Please find out more about the product by calling 1-844-353-9839 or visit [www.ftsyn.com](http://www.ftsyn.com). The PRO20 logo is a registered trademark of FT Synthetics Inc.



**FT SYNTHETICS**

Toll Free Ph: 1-844-353-9839  
Phone: 604-594-3439  
Fax: 604-594-3589  
[www.ftsyn.com](http://www.ftsyn.com)