



NEXGENTM
SYNTHETICS

ALL TEMP. ALL WEATHER
PERFORMANCE

AnchorDeckTM is a next generation synthetic roofing underlayment for sloped roof applications.

AnchorDeckTM coating technology allows underlayment to be anchored to the deck prior to applying fasteners. Innovative high-traction walking surface, excellent durability and many other unique performance features make AnchorDeckTM the smart choice for todays roofing professionals.

AnchorDeckTM is designed for use under asphalt shingles, metal in residential applications, synthetic shingles and primed cedar shakes. AnchorDeckTM meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES. AnchorDeckTM not only protects your roof deck, it helps protect Roofers as well.

Ask for it at your nearest roofing distributor today.



- AnchorDeckTM has a unique coating technology which allows underlayment to be anchored to the deck prior to applying fasteners.
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- *No stretching around fasteners & no blow-offs!
- Innovative high traction walking surface
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA A123.3
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- High Definition (HD) printing
- 90 Days UV Exposure
- 20 year warranty



**PRINT
YOUR LOGO[®]
HERE!**

*Attract new customers and increase
awareness in your local area!*

Visit:
www.roofnado.com/dual-logo
for more information

20 Year
LIMITED WARRANTY



 **Roofnado.com**
Sentry Building Innovations
1209 Orange Street, Wilmington,
New Castle, Delaware 19801
Customer Service: 1-843-735-1773

Test/Standard*

Tensile Strength ASTM D5034
Tear Strength ASTM D4533
Liquid Water Transmission ASTM D4869
Fire Rating ASTM E108
UV Exposure
Temperature Range

Typical Value

MD 95 lbs (43 kg) | CD 85 lbs (38.5 kg)
MD 18 lbs (8.16 kg) | CD 16 lbs (7.26 kg)
Pass
Class A
3 Months
-40° F - 212° F

Roll/Pallet Specs

Length per roll: 286' / 87 m
Width per roll: 42" / 1.1 m
Weight per roll: 23 lbs / 10.4 kg
Roll size: 10 sq / 93 m²
Rolls per pallet/truck: 49 / 1,764
Pallet weight: 1,177 lbs / 534 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.
ENG-RN-AD-DIGITAL R8 NOV2019

†When correctly installed as per AnchorDeck™ installation instructions. All Roofnado™ product installation instructions are available to download or view from our website: www.roofnado.com