



1.877.MAMMOUTH www.soprema.ca

TECHNICAL DATA SHEET 150526SCAN1E

(supersedes 130429SCAN1E)

# ALSAN RS CATALYST POWDER

#### **DESCRIPTION**

ALSAN RS CATALYST POWDER is a reactive agent based on dibenzoyl peroxide used to induce curing of all ALSAN RS resin products during membrane application.

COLOR: ALSAN RS CATALYST POWDER is supplied as a white powder.

#### **APPLICATION**

**MIXING**: Using a slow-speed (200 to 400 rpm) mechanical agitator, thoroughly mix the entire container of resin for two minutes before each use, and prior to pouring off resin into a second container if batch mixing. Catalyze only the amount of material that can be used within 10-15 minutes. Add pre-measured catalyst to the resin component, stir for two minutes and apply to substrate. Refer to individual product data sheets for specific recommendations and requirements for the resin being used.

The amount of catalyst added to ALSAN RS resins varies based on the resin type, weight of the resin and temperature.

## PACKAGING

ALSAN RS CATALYST POWDER is available in prepackaged 0.1 kg packets.

### **STORAGE & HANDLING**

Shelf life: 12 months, properly stored in original unopened containers. For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).

Always store closed containers in cool, ventilated and dry location away from flame sources. **Do not store in direct sunlight above** 25 °C (77 °F). For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).

TDS\_ALSAN\_RS\_CATALYST\_POWDER.indd

YSTÈME ENVIRONNEMENT

**ISO 1400**1

