

ELASTOFLEX® S6 G

SBS GRANULATED CAP SHEET

PRODUCT DESCRIPTION

Elastoflex S6 G membranes are high quality Styrene-Butadiene-Styrene (SBS) modified asphalt roofing membranes specially designed with a sanded back for hot mop or cold process applications or with a polyethylene burn-off film for heat welded applications. Reinforced with a superior polyester membrane, the Elastoflex S6 G exhibits exceptional tensile strength and puncture resistance. The granulated surface provides superior long-term UV protection. Manufactured for the commercial, industrial and residential markets, the proprietary SBS asphalts and product composition will offer long-term dimensional stability, flexibility and resistance to moisture.

The top surface of the Elastoflex S6 G membrane has a granular finish available in a variety of colors. The membrane is free of granules along the selvage edge; the roll ends feature patented FASTLap® technology to provide for a sand-free edge for ease of application.

USES

- High-quality SBS modified, granule surfaced for single or multi-ply systems
- New roofing, re-roofing and re-cover roofing and flashing details
- Hot asphalt, cold process or heat-welded installation methods

FEATURES AND BENEFITS

- Exceptional long-term weathering performance
- Superior flexibility, puncture resistance and dimensional stability
- Ease of application over broad spectrum of substrates and conditions

TECHNICAL DESCRIPTION

TEST METHOD	PROPERTY	ASTM VALUE
ASTM D5147	Peak Load @ 23+/-2°C (73.4+/-3.6°F), MD and XMD, min, kN/m (lbf/in.)	8.8 (50)
ASTM D5147	Elongation @ 23+/-2°C (73.4+/-3.6°F), MD and XMD, min (%)	35
ASTM D5147	Tear Strength @ 23+/-2°C (73.4+/-3.6°F), min, N (lbf)	246 (55)
ASTM D5147	Low Temperature Flexibility, max, °C (°F)	-18 (0)
ASTM D5147	Granule Embedment, g	2

AVAILABLE COLORS

Top surface granule protection is available in a variety of colors such as:

Black Buff Chestnut Grey Slate Heather Blend
 Oak Pine Green White Red Blend Weatherwood



PRODUCT DATA

Coverage (Nominal) 100 sq ft
 Weight (Approx) 102 lbs
 Thickness 4.0; 160 mils
 Roll Size 32'10" X 39 3/8" (10m x 1m)
 Rolls/Pallet 20

APPLICABLE STANDARDS

- ASTM D6164 Type I
- Miami Dade Code Compliance
- Factory Mutual Approved
- UL Classified for use in class A, B or C roofs, as listed the latest UL "Roofing Materials and Systems Directory"
- ICC ESR-2018
- TDI



PRODUCT WARRANTY

Polyglass U.S.A., Inc. commercial roofing membranes can be backed with a manufacturer's warranty for up to 20 years when used as part of an approved, multi-ply roofing system. Please see your Polyglass U.S.A., Inc. Sales or Technical Representative for specifications and details.



www.polyglass.us

ELASTOFLEX® S6 G

SBS GRANULATED CAP SHEET

APPLICATION INSTRUCTIONS

Elastoflex S6 G is intended to be used as the primary weathering surface in new or re-roof applications. Elastoflex S6 G is to be applied as the uppermost layer of a multi-ply roof system applied over a compatible Polyglass base or interply membrane. Elastoflex S6 G may be applied directly to certain non-combustible substrates.

- Apply over clean, dry, dust and debris-free substrates. Prime concrete decks prior to application with PG 100 Asphalt Primer.
- When re-roofing, remove all prior roofing materials down to a clean debris-free substrate and properly close-off all abandoned roof penetrations.
- Concrete or steel decks shall be designed with proper expansion devices.
- Wood decks shall have all joints blocked and properly supported.
- Ensure the fire rating of the assembly over any combustible substrate.
- Ensure the installation of Elastoflex S6 G does not prevent the ventilation of existing construction.
- Do not apply over shingles or any granulated surface.
- While installing Elastoflex S6 G:
 1. Start at the low point of the roof.
 2. Unroll the material and allow to relax.
 3. Install in a solid mopping of Type III or Type IV asphalt, PG 350 Mod Bit Adhesive, or torch.
 4. Position successive rolls providing a minimum 6" end lap and 3" side lap.
 5. Matching loose granules may be sprinkled into the bleed out.
- Details and flashing may be installed using hot asphalt or cold application techniques. Check project details for proper installation requirements.

POLYGLASS U.S.A., INC. MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330
Customer Service: (800) 222-9782
Technical Service: (866) 802-8017

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 5 years. Refer to material safety data sheet (MSDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control.

For most current product data and warranty information, visit www.polyglass.us

Copyright ©2015 by Polyglass U.S.A., Inc and all rights are reserved
Edition Date: 05/15 • Doc# Elastoflex S6 G



www.polyglass.us