



# PLATINUM

*A New Generation of Underlayments*

## TECHNICAL DATA SHEET

FT SYNTHETICS PLATINUM		
General Specifications		
	PLATINUM	30 Lb. Felt
Width inch	48	36
Weight per roll	35 Lb.	45 Lb.
Length in feet	250	72
Rolls per Pallet ( 48 x 48)	36	25
Rolls per Truckload - 34 Skids	1224	1000
Rolls Required per 1,000 Sq feet	1	5
100% recyclable	Yes	No
Material Composition	Polyolefin	Asphalt
UV Resistance	6 Months	None
Breaking Strength ASTM D 5034 MD	114.6 lb (52.0 kg)	NA
Breaking Strength ASTM D 5034 CD	112.4 lb (51.0kg)	NA
Tear Strength ASTM D4533 MD	81.8 lb (37.1kg)	NA
Tear Strength ASTM D4533 CD	88.2 lb (40.0 kg)	NA
Water shower Exposure ASTM D 4869	Pass	NA
Permeability ASTM E96	<0.05 Perms	1.75 Perms
Mullen Burst ASTM D751-06	156 psi	NA
Nominal Thickness ASTM D1777	20 mils	60 mils
Temperature Range	-40°F to 240°F	
Enhanced Slip Resistant Surface	GRIPSPOT™ or plain	Basic
Color	Varies	Black
Custom Printing	Available	None
Warranty	40 Years	None

The Data shown above is based on the test averages and independent test reports. There can be a +/-10% variation in the individual test results. This report should not be considered as a warranty for the manufacturer. The manufacturer is not responsible for the misrepresentation or misinterpretation of the data by the reader. Please find out more about the product by calling 1-844-353-9839 or visit [www.ftsyn.com](http://www.ftsyn.com). GRIPSPOT™ is a trademark of FT Synthetics Inc.

ASTM D226-97  
ASTM D4869  
CAN/CSA A123.3



CAN/ CSA A220.1  
ASTM E108  
CCRR 1028  
AC188



12179 - 86th Avenue  
Surrey BC V3W 3H8  
Canada

Toll Free Ph: 1-844-353-9839  
Phone: 604-594-3439  
Fax: 604-594-3589  
[www.ftsyn.com](http://www.ftsyn.com)