


### TECHNICAL DETAILS

<b>WIDTH ± 1/8"</b> 13 1/4" 337 mm	<b>LENGTH ± 1/4"</b> 39" 0.99 m
<b>EXPOSURE</b> 5 5/8" 143 mm	<b>GRANULE ADHESION</b> 0.35 g Typical Results
<b>SHINGLES/SQUARE</b> 66 3 bundles/square	<b>SQUARES/PALLET</b> 16

### TEST COMPLIANCE

<b>ASTM</b> D7158 Class H	<b>ASTM</b> D3462
<b>ASTM</b> D3161 Class F	<b>ASTM</b> D3018 Type I
<b>ASTM</b> E108 Class A Fire Rating	<b>CSA</b> A123.5
<b>ICC-ES ACCEPTANCE</b> AC438	

### FEATURES & BENEFITS

- Sustainable NEX<sup>®</sup> asphalt technology
- Exceptional all-weather performance
- 3M<sup>™</sup> Smog-Reducing Granules
- Larger nailing area of The Zone<sup>®</sup>
- Double rain seal protection
- Algae Resistant System Warranty
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties



## NEX<sup>®</sup> POLYMER MODIFIED LAMINATED ARCHITECTURAL SHINGLES



### PRODUCT USE

The 242 Highlander<sup>®</sup> NEX<sup>®</sup> AR is a laminated, algae-resistant asphalt shingle fortified with sustainable NEX<sup>®</sup> polymer modified asphalt technology for enhanced granule adhesion and increased weather protection. Highlander<sup>®</sup> NEX<sup>®</sup> AR features the exclusive nailing accuracy-enhancing design of The Zone<sup>®</sup>, a larger nailing area that dramatically improves correct fastener placement. Please consult Malarkey's Technical Services Department for approval of roof systems.

### COMPOSITION & MATERIALS

Highlander<sup>®</sup> NEX<sup>®</sup> AR is manufactured on a non-woven fiberglass mat and coated on both sides with NEX<sup>®</sup> polymer modified bitumen (asphalt) that is compounded with a fire-retardant mineral stabilizer. Its surface incorporates an innovative combination of ceramic granules that provide varied color, weatherability, algae protection, even smog reduction.

### APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions, in three languages, are available on the shingle wrapper by scanning the corresponding Quick Response (QR) code, on our website at [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM), or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

### PRECAUTION

For best results, Malarkey recommends Highlander<sup>®</sup> NEX<sup>®</sup> AR be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), a double layer of underlayment is required (IBC & IRC have an exception for a single layer of ASTM D1970 underlayment in lieu of a double layer). Highlander<sup>®</sup> NEX<sup>®</sup> AR has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. On slopes greater than 21" (533 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

### WARRANTY

Malarkey Roofing Products<sup>®</sup> offers various warranties to meet specific requirements. The warranty packages available for Highlander<sup>®</sup> NEX<sup>®</sup> AR include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Highlander<sup>®</sup> NEX<sup>®</sup> AR also features a 10-year Algae Resistant System Warranty from Malarkey. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Highlander<sup>®</sup> NEX<sup>®</sup> AR and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products<sup>®</sup> Inventory SKU numbers for this product: 242 Highlander<sup>®</sup> NEX<sup>®</sup> AR

#### TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm Pacific Time  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

#### CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191  
Portland, OR 97217-7472 or 800.545.1191  
P.O. Box 17217 Fax: 503.289.7644  
Portland, OR 97217-0217