PABCO Prestige®

Technical Data Sheet



If you want an upgraded traditional laminated shingle, choose PABCO Prestige[®]. A combination of a heavyweight, laminated shingle with select color choices, PABCO Prestige provides the options you need, backed by an industry leading warranty.

Our heavyweight glass mat is saturated with quality asphalt and coated with colored mineral granules to produce 11 color options. Cut with our tapered design to help alleviate debris and patterning, two layers are then laminated together to develop the appearance PABCO Prestige. Choose this architectural shingle for the standard of excellence.

TECHNICAL DETAIL	DATA
Category	Architectural Laminated Fiberglass
Weight per Square (nominal)	295 lbs
Weather Exposure	5 5/8"
Offset	5 5/8" (may be applied L to R, or R to L)
Shingles per Square (approx.)	64
Bundles per Square (approx.)	4
Bundles per Pallet	60

WARRANTY*	
Original Homeowner	Limited Lifetime
Subsequent Homeowners	50 Years Fully Transferable
Non-Prorated Coverage	15 Years
Wind Resistance (Standard Application 110 mph)	15 Years
Wind Resistance (High Wind Application – 130 mph)	15 Years
Algae Resistance (Featuring Algae Defender®)	Limited Lifetime

DESIGNATION NUMBER	APPLICABLE STANDARD
ASTM D3462	Standard Specification for Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
ASTM D3018	Type I Standard Specification for Class A Asphalt Shingles Surfaced with Mineral Granules
CSA Standard A123.5	Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules
UL 790	Class A Fire Resistance
ASTM E108	Class A Fire Resistance
ASTM D3161	Class F Wind Resistance
ASTM D7158	Class H Wind Resistance
ESR-1717	ICC-ES Evaluation Report



Detailed Installation instructions at www.pabcoroofing.com/literature.

^{*}Single Family Residences only. See PABCO®'s Limited Shingle Warranty for details and other structures.