



3812 E. 91st, Cleveland, OH 44105
Tel: (800) 350.2142
Fax: (800) 350.2307

VIKING™ UDL PRO GRADE *Ice & Water Shield*

Uses & Description

VIKING UDL PRO GRADE Ice & Water shield is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. VIKING UDL PRO GRADE Ice & Water is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

Product Benefits

- Offers a skid resistant, granular surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights

Specifications

Reference ASTM	ASTM D 1970
Thickness, Min	55 mils
Maximum Load, Min	MD=35 CD=35
Elongation at Break, Min	30%
Adhesion to Plywood @ 77 °F Min	30.0 lbf/ft
Thermal Stability, Max	0.05
Flexibility Temperature, @ -20 °F Min	pass
Sealability Around Nail	pass
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of Lap Seam	pass
Slip Resistance	pass
Rolls per Pallet (box)	20
Roll Weight	72 lbs ±
Roll Diameter	8.75 in.
Square Feet / Roll	200
Available Roll Dimensions	36" x 66.8'