



3812 E. 91st, Cleveland, OH 44105  
Tel: (800) 350.2142  
Fax: (800) 350.2307

## VIKING™ UDL METAL

### Uses & Description

VIKING™ UDL METAL is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. It's non-abrasive polyester surface is excellent for use in tile and metal applications.

### Benefits

- Offers a skid resistant, polyester surface.
- Silicone-treated, split-back, release film allows for easy installation and handling.
- Softening point is a minimum of 250°F
- May be installed directly to concrete, plywood, wood composition board and gypsum.
- Self seals around nails.
- May be used in new construction or re-roofing.
- Offers greater tear resistance than traditional felt underlayment.
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights.
- Provides excellent low temperature flexibility.
- May be left exposed up to 90 days prior to application of finished roof.
- Florida Approval (FL #13671)

### Specifications

ASTM D 1970	
Thickness, Min	60 mils
Maximum Load, Min	MD=80 CD=40
Elongation at Break, Min	30%
Adhesion to Plywood @ 77 °F Min	30.0 lbf/ft
Thermal Stability, Max	0.05
Flexibility Temperature, @ -20 °F Min	pass
Sealability Around Nail	pass
Water Proof Integrity after Low Temp. Flex	pass
Waterproof Integrity of Lap Seam	pass
Slip Resistance	pass
Rolls per Pallet (box)	20
Roll Weight	65 lbs ±
Roll Diameter	8.5 in.
Square Feet / Roll	200
Available Roll Dimensions	36" x 66.8'