

**TECHNICAL DETAILS**

|   |  |
|---|--|
| <b>WEIGHT/SQUARE</b><br>275 lbs.<br>124.8 kg                      | <b>EXPOSURE</b><br>5 <sup>5</sup> / <sub>8</sub> "<br>142.9 mm |
| <b>SHINGLES/SQUARE</b><br>64<br>4 bundles/square                  | <b>GRANULE ADHESION</b><br>0.35 g<br>Typical Results           |
| <b>WIDTH ± 1/8"</b><br>13 <sup>1</sup> / <sub>4</sub> "<br>337 mm | <b>LENGTH ± 1/4"</b><br>40"<br>1.02 m                          |
| <b>SQUARES/PALLET</b><br>12                                       |  |

**FLEXOR™ SBS POLYMER  
MODIFIED LAMINATED  
ARCHITECTURAL SHINGLES**



**TEST COMPLIANCE**

|  |   |
|--|---|
| <b>ASTM</b><br>D7158<br>Class H            | <b>ASTM</b><br>D3462  |
| <b>ASTM</b><br>D3161<br>Class F            | <b>ASTM</b><br>D3018<br>Type I  |
| <b>ASTM</b><br>E108<br>Class A Fire Rating | <b>UL RATING</b><br>2218<br>Class 4   |
| <b>CSA</b><br>A123.5                       | <b>ICC APPROVAL</b><br>ESR-3150   |
| <b>FBC APPROVAL</b><br>#14809              |  |

**FEATURES & BENEFITS**

- Scotchgard™ Protection from 3M
- Extreme Weather Protection
- Superior Granular Embedment
- Flexor™ SBS Polymer Modified Asphalt
- The Zone® Nailing Area
- All-Weather Flexibility
- Double Rain Seal Protection
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties

**PRODUCT USE**

The Legacy® shingle and Legacy® featuring Scotchgard™ are laminated asphalt shingles fortified with Flexor™ SBS polymer modified asphalt technology for extreme weather protection. They are to be used whenever increased flexibility, architectural design, tensile strength, and tear-resistance in shingles is desired. The Legacy® line features the exclusive nailing accuracy-enhancing design of The Zone®. The larger nailing area of The Zone® dramatically improves correct fastener placement. The smaller nailing area found in a majority of other shingles leads to poor fastener placement and results in improper installations which may void warranties.

**COMPOSITION & MATERIALS**

The Legacy® is a mineral-surfaced, self-sealing, laminated architectural shingle with a Flexor™ SBS polymer modified asphalt coating and fire retardant fillers on a woven fiberglass mat. Legacy® featuring Scotchgard™ is surfaced with embedded, Scotchgard™ algae resistant granules.

**APPLICATION**

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper, at [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM), or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

**PRECAUTION**

For best results, Malarkey recommends The Legacy® shingle line be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), additional deck protection is required. The Legacy® shingle line has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. In high wind areas and on slopes greater than 12" (305 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

**WARRANTY**

Malarkey Roofing Products® offers various warranties to meet specific requirements. The warranty packages available for the Legacy® shingle line include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Legacy® featuring Scotchgard™ also carries a 20-year Scotchgard™ warranty against algae growth. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

The Legacy® shingle line and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) Inventory SKU numbers for this product: 272 Legacy® and 273 Legacy® featuring the Scotchgard™ Algae Resistant Shingle Protector from 3M

Effective 5/15  
Supersedes all previously published data  
Check for most current version on our website.

**TECHNICAL ASSISTANCE:**  
Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

**CORPORATE OFFICE:**  
3131 N. Columbia Blvd. Telephone: 503.283.1191  
Portland, OR 97217-7472 or 800.545.1191  
P.O. Box 17217 Fax: 503.289.7644  
Portland, OR 97217-0217