


## Landmark® Shingles

### PRODUCT INFORMATION

Landmark® shingles reflect the same high manufacturing standards and superior warranty protection as the rest of CertainTeed's line of roofing products. Landmark (and Algae Resistant-AR) shingles are built with the industry's toughest fiber glass mat base, and their strict dimensional tolerance assures consistency. Complex granule color blends and subtle shadow lines produce a distinctive color selection. Landmark is produced with the unique NailTrak® nailing feature.



Landmark algae-resistant (AR) shingles are algae-resistant and help protect against dark or black discoloration, sometimes called staining or streaking, caused by blue-green algae. AR shingles are not available in all regions.

**Colors:** Please refer to the product brochure or CertainTeed website for the colors available in your region.

**Limitations:** Use on roofs with slopes greater than 2" per foot. Low-slope applications (2:12 to < 4:12) require additional underlayment. In areas where icing along eaves can cause the back-up of water, apply CertainTeed WinterGuard® Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

**Product Composition:** Landmark shingles are composed of a fiber glass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. Two pieces of the shingle are firmly laminated together in a special, tough asphaltic cement. All Landmark shingles have self-sealing adhesive strips.

### Applicable Standards

ASTM D3018 Type I	ICC-ES ESR-1389 and ESR-3537
ASTM D3462	CSA Standard A123.5 (Regional)
ASTM E108 Class A Fire Resistance	Miami-Dade Product Control Approved (Regional)
ASTM D3161 Class F Wind Resistance	Florida Product Approval # FL5444
ASTM D7158 Class H Wind Resistance	Meets TDI Windstorm Requirements
UL 790 Class A Fire Resistance	

### Technical Data:

	Landmark (and AR)
Weight/Square (approx.)	217 to 229 lb *
Dimensions (overall)	13 1/4" x 38 3/4"
Shingles/Square (approx.)	66
Weather Exposure	5 5/8"

\*Dependent on manufacturing location

## **INSTALLATION**

Detailed installation instructions are supplied on each bundle of Landmark shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

**Hips and Ridges:** For capping hip and ridge apply CertainTeed Shadow Ridge®, Cedar Crest® or Mountain Ridge® shingles of a like color.

## **MAINTENANCE**

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

## **WARRANTY**

Landmark (and AR) shingles carry a lifetime limited, transferable warranty to the consumer against manufacturing defects when applied to stated CertainTeed application instructions for this product. In addition, Landmark (and AR) carry up to 10-years of SureStart™ Protection. Landmark AR shingles carry a 10-year algae resistance warranty. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at [www.certainteed.com](http://www.certainteed.com)).

## **TECHNICAL SUPPORT**

Technical Service Department: 800-345-1145  
e-mail: [RPG.T.Services@saint-gobain.com](mailto:RPG.T.Services@saint-gobain.com)

## **FOR MORE INFORMATION**

Customer Experience Team: 800-233-8990  
e-mail: [gethelp@saint-gobain.com](mailto:gethelp@saint-gobain.com)  
Web site: [www.certainteed.com](http://www.certainteed.com)

**CertainTeed**  
20 Moores Road  
Malvern, PA 19355

